

SPRING SPECIFICATION (B&D Australia)

Part No.: 62967 Page: 1 of 2

TRACK FITTING SELECTION CHARTS

Date: 21 Sept 2010 Issue: 1

		Single Spring/Side				Double Spring/Side					
Door Height (mm)	2851 min					120-T-3050 Orange Spring	175-T-3050 Orange Spring		3050 max		Door Height (mm)
	2850 max							2701 min			
	2451 min					120-T-2700 Orange Spring	175-T-2700 Orange Spring		2700 max		
	2450 max	70-T-2450 Brown Spring	100-T-2450 Brown Spring				2401 min				
	2251 min					120-T-2400 Brown Spring	175-T-2400 Brown Spring		2400 max		
	2250 max	70-T-2250 Brown Spring	100-T-2250 Brown Spring				2101 min				
	1951 min					120-T-2100 Brown Spring	175-T-2100 Brown Spring		2100 max		
	1950 max	70-T-1950 Brown Spring	100-T-1950 Brown Spring				1900 min				
	1800 min										
	Door Weight (kg)	30	70	71	100	101	120	121	175	Door Weight (kg)	

SPRING SPECIFICATIONS

Colour	Wire Dia.	Spring OD	Active Length
JAMB FITTING			
Green	5	38	695
Black	6	43.6	740
TRACK FITTING			
Brown	5.6	41	542
Orange	5.6	41	695

JAMB FITTING SELECTION CHART

Door Height (mm)	2250 max	70J & 70J S/Fix Green Spring		90J Black Spring	
	1850 min				
	Door Weight (kg)	30	70	71	90